



NATIONAL POWER CORPORATION
 Small Power Utilities Group
 Luzon Operations Department

**REQUEST FOR QUOTATION FORM
 (SHOPPING)**

(Supplier's Name/Address/Fax No.)

P.R. No.: S0-SPU10-008

(Please use P.R. No. to identify offer/Letters)

No. of Page(s) (including this sheet): 3pages

MADAM/SIR:

PLEASE PRESENT YOUR LOWEST OFFER FOR THE SPECIFIED GOODS IN THE ATTACHED PR AND SIGNIFY YOUR ACCEPTANCE OF THE TERMS AND CONDITIONS AS STATED HEREIN BY SIGNING ON THE SPACE PROVIDED BELOW. THUS, KINDLY SUBMIT THE SIGNED COPY TOGETHER WITH YOUR SEPARATE LETTER QUOTATION IN A SEALED ENVELOPE DIRECTLY TO THE **UNDERSIGNED OR FAX TO 9278624 / 9206120 LOC 3138** ON OR BEFORE **10:00 AM/MAY 3, 2010**. OPENING WILL BE ON 10:00 AM/MAY 4, 2010.

IN CASE OF A FAILED CANVASS DUE TO INSUFFICIENT NO. OF COMPLYING OFFERS, A RE-CANVASS MAYBE CONDUCTED IF THERE IS STILL ADEQUATE TIME TO DO SO WITHOUT JEOPARDIZING THE URGENT NEED/DELIVERY OF THIS PARTICULAR MATERIALS/SUPPLIES REQUIREMENT.

Very truly yours,


EMMARIE JAYNE E. MANAY
 Materials Management Specialist C

INSTRUCTION TO SUPPLIERS:

- Indicate if the offer is VAT EXCLUSIVE or VAT INCLUSIVE and must coincide if VAT or NON-VAT
- Late Offer will not be accepted.

FIXED TERMS:

DELIVERY PERIOD:	PAYMENT: 30 – 45 DAYS
PRICE VALIDITY : 60 DAYS	WARRANTY:

ADDITIONAL TERMS AND CONDITIONS

In case of award, supply shall be covered by standard Warranties for Special Tools/Instruments/Equipment and major parts submitted upon delivery. Further, for late delivery not caused by fortuitous event, NPC shall impose penalty charges an amount equal to 1/10 of 1% of the cost of the unperformed portion for every day of delay until actual performance but not to exceed 10% of the total contract price.

TERMS AND CONDITIONS ACCEPTED:

SUPPLIER'S AUTHORIZED REPRESENTATIVE
 (SIGNATURE OVER PRINTED NAME/DATE/DESIGNATION)

REPUBLIC OF THE PHILIPPINES
NATIONAL POWER CORPORATION
NPC AGHAM RD

OP-10-1773
NON-OMA



PR NO. SO-SPU10-008
Use this Number in all communication

PURCHASE REQUISITION

Requisitioning Office : OVP-SMALL POWER UTILITIES GROUP
 Cost Center Number : 5800000 Local : 5241
 GL No. : 385 / 077 OE No. : _____
 WO No. : _____ JO No. : _____

Date : 03/30/10
 Date Needed : 06/28/10
 Deliver to : _____
 Date PR Rcvd. by Proc Office: _____

ITEM NO.	NSN	COMPLETE DESCRIPTION/SPECIFICATION	QUANTITY	U/M	ESTIMATED COST	ASSIGNED PO/IO NO.
1	N00000003	HARD DISC PORTABLE, 1 TERABYTE (NETWORK ATTACHED STORAGE)	1	PC	9,000.00	
2	N00000001	SCANNER (HS PER ATTACHED SPECS)	1		240,000.00	
					PHP	249,000.00

NOV 20 BY:
[Signature]
 MANANSALA, R. IV
 IS/IT REP

Approved:
[Signature]
F. A. TAMPINCO
 President

CERTIFIED FUNDS AVAILABLE
2010 CC NO. 80000
 EX NO. 077 GPE NO. 385

Certification of Funds Availability
[Signature]
A. P. JAPON
 Manager Finance

Included in the PPMP
[Signature]
M. S. CHIU
 VICE-PRESIDENT, SPUG

PURPOSE/REMARKS TO BE USE AT OVP OFFICE


Attachments : PPMP, SPECS	Requisitioned by : <i>[Signature]</i> M. C. M. DALANGIN Print Name & Position SECRETARY C	Approved for Purchase : <i>[Signature]</i> M. S. CHIU Print Name & Position VICE PRESIDENT
	Date <u>3/30/10</u>	Date

[Handwritten signature]

SPECIFICATION

	Desktop sheetfed scanner	
Document Feeding	Automatic or manual sheet feeding	
Document size		
Width	53 - 219mm (2.08 - 8.6in.)	
Length	70 - 356mm (2.75 - 14in.)	
	Long Document Mode:	up to 1,000mm (39.3in.)
Document thickness and weight		
U-Turn path	Automatic feeding:	0.06 - 0.15mm, 52 - 128g/m ² (14 - 32lb. bond)
	Manual feeding:	0.05 - 0.2mm, 42 - 157g/m ² (11 - 40lb. bond)
Straight path	Automatic feeding:	0.06 - 0.15mm, 52 - 128g/m ² (14 - 32lb. bond)
	Manual feeding:	0.05 - 0.66mm, 42 - 546g/m ² (11 - 144lb. bond)
Business card size and thickness		
Size	53.9 x 85.5mm (2.12 x 3.37in.)	
Thickness	0.76 ± 0.08mm (0.03 ± 0.003in.)	
Feeding Capacity	10mm stack or 100 sheets of 80g/m ² (20lb. bond)	
Scanning Element	3-line CMOS CIS	
Light Source	LED (red, green, and blue)	
Scanning Side	Simplex / Duplex	
Scanning Modes	Black and White, Error Diffusion, High-Speed Text Enhancement, Advanced Text Enhancement (2 types) 256-level Greyscale 24-bit Colour, Auto Image Type Detection	
Scanning Resolutions	100 x 100dpi, 150 x 150dpi, 200 x 200dpi, 240 x 240dpi, 300 x 300dpi, 400 x 400dpi, 600 x 600dpi	
Scanning speed (A4 / LTR, Portrait, 200dpi)		
Black and White	Simplex:	40ppm
	Duplex:	80ipm
256-level Grayscale	Simplex:	40ppm
	Duplex:	80ipm
24-bit Colour	Simplex:	40ppm
	Duplex:	80ipm
Interfaces	SCSI-III / Hi-Speed USB 2.0	
Scanner driver	ISIS / TWAIN	
Useful functions	Job Function, Folio, Ultrasonic Double Feed Detection, Rapid Recovery System, Moire Reduction, Prevent Bleed Through / Remove Background, Punch Hole Removal, Colour Dropout, Batch Separation, Automatic Page Size Detection, Text Orientation Recognition, Skip Blank Page, Deskew, Gamma, Multistream™, Prescan, User Preferences	
Power requirements	AC100 - 120V (50 / 60Hz), AC220 - 240V (50 / 60Hz)	
Power Consumption	25W maximum power (3W max. during standby)	
Operating Environment	10 - 32.5°C (50 - 90.5°F)	
	Humidity:	20 - 80% RH
Dimensions (W x D x H)	Feed trays closed:	318 x 278 x 187mm (12.5 x 10.9 x 7.3in.)
Weight	Approx. 6.4kg (14.1lb.)	
Options / Consumables	Barcode Module II, Exchange Roller Kit (includes roller unit and retard roller)	

Noted by:


M. S. CHIU
 Vice President, SPUG

